


# Data Equipment Protector



- Models to cover RS-232, RS-423, RS-422 and RS-485 protocols
- Designed to provide both line to signal-ground and signal-ground to protective-earth protection
- Plug-in protection is simple to install



Part Number	DEPRS2322525D	DEPRS23299D	DEPRS42299D
Nominal Discharge Current (In)	300 A 8/20 $\mu$ s		400 A 8/20 $\mu$ s
Max Continuous Operating Voltage (Uc)	15 VDC		9 VDC
Capacitance	30 pF Max		
Protection Modes	All pins to ground		
Connection Type	DB25, Male/Female	DB9, Male/Female	
Depth (D)	61 mm		
Height (H)	16.6 mm		
Width (W)	53.5 mm	30.5 mm	
Unit Weight	0.077 kg	0.054 kg	

## WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.erico.com](http://www.erico.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2021 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.