


DIN Rail Filter Module



- Secondary surge protection and filtering
- DIN rail mount provides simple installation



Part Number	DFM20A	DFM63A
Rated Load Current (IL)	20 A	63 A
Max Continuous Operating Voltage (Uc)	275 VAC	
Frequency	50 – 60 Hz	
Connection, Solid	1 – 6 mm ²	1 – 35 mm ²
Connection, Stranded	1 – 6 mm ²	1 – 25 mm ²
Enclosure Material	UL® 94V-0 Thermoplastic	
Enclosure Rating	IP 20 NEMA®-1	
Mounting	35 mm top hat DIN rail	
Module Width	4 M	
Temperature	-35 to 55 °C	
Unit Weight	1.57 kg	
Depth (D)	68 mm	
Height (H)	90 mm	
Width (W)	72 mm	

NEMA is a registered service mark of National Electrical Manufacturers Association. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2021 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.