


Universal Transient Barrier, Single Pair



- Compact design universal transient barrier provides protection of low-voltage circuits and transducers
- Separate plug and base design allows hot swappable module replacement
- Multi-stage protection and fine over-voltage protection helps ensure lowest residual surge voltages reach sensitive equipment
- Common-mode and differential-mode protection protects against both possible surge conditions
- Surge rating to 20 kA 8/20 μ s is ideal for exposed wiring
- Allows for protection of 25 analog signals or 50 digital signals per linear foot (0,3 m) of DIN rail space



Part Number	UTB5SP	UTB30SP	UTB110SP	UTB60SP	UTB15SP
Article Number	702861	702863	702866	702864	702862
Nominal System Voltage (Un)	0 - 3 VAC 0 - 5 VDC	10 - 21 VAC 15 - 30 VDC	100 - 120 VAC 60 - 154 VDC	21 - 42 VAC 30 - 60 VDC	3 - 10 VAC 5 - 15 VDC
Max Continuous Operating Voltage (Uc)	5 VAC 7 VDC	23 VAC 33 VDC	150 VAC 170 VDC	45 VAC 64 VDC	12 VAC 18 VDC
Rated Load Current (IL)	2 A				
Frequency	0.5 MHz	2.0 MHz	3.0 MHz		1.0 MHz
Loop Resistance	1 Ω				
Max Discharge Current (Imax), L+L-PE	20 kA 8/20 μ s				
Protection Modes	Common Differential				
Technology	Gas Discharge Tube (GDT) Metal Oxide Varistor (MOV) Silicon Avalanche Diode (SAD)				
Voltage Protection Level (Up), L-L	10 V @ 3 kA	44 V @ 3 kA	220 V @ 3 kA	85 V @ 3 kA	25 V @ 3 kA
Connection, Stranded	1 - 4 mm ²				
Mounting	35 mm top hat DIN rail				
Temperature	-20 to 65 °C				
Enclosure Material	UL [®] 94V-0 Thermoplastic				
Enclosure Rating	IP 20 NEMA [®] -1				
Depth [D]	72 mm				
Height [H]	90 mm				

Part Number	UTB5SP	UTB30SP	UTB110SP	UTB60SP	UTB15SP
Width (W)	12 mm				
Unit Weight	0.07 kg				
Certification Details	UL® 497B				
Complies With	ANSI®/IEEE® C62.41.2-2002 Cat A, Cat B, Cat C				
Replacement Module	UTB5SPM	UTB30SPM	UTB110SPM	UTB60SPM	UTB15SPM

ANSI is a registered trademark of American National Standards Institute. IEEE is a registered trademark of The Institute of Electrical and Electronics Engineers, Inc. NEMA is a registered service mark of National Electrical Manufacturers Association. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2021 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.